

Building Specification Wood-Cement Permanent Formwork Walling Units

Wood-Cement Permanent Formwork Walling Units

Manufacturer: Durisol UK Ltd
Parkway, Pen-Y-Fan Industrial Estate, Crumlin,
NP11 3EL
01495 249400

Product reference: D365

- Thermal conductivity (maximum) certified by UKAS accredited laboratory at BM TRADA – U 0.19
- Work sizes (length x height x thickness): 500 x 250 x 365mm
- Bond: Stretcher
- Installation: Dry laid, without a mortar joint, so vertical & horizontal voids are aligned. Insulation to outside
- Concrete Fill: to BS EN 206 - flow class not higher than F5
 - Concrete: C30 or to Engineers specification
 - Slump between 180-220mm
 - Width of concrete fill: 120mm
 - Reinforcement: To engineer's drawings

Wood-Cement Permanent Formwork Walling Units

Manufacturer: Durisol UK Ltd
Parkway, Pen-Y-Fan Industrial Estate, Crumlin,
NP11 3EL
01495 249400

Product reference: D300

- Thermal conductivity (maximum) certified by UKAS accredited laboratory at BM TRADA – U 0.27
- Work sizes (length x height x thickness): 500 x 250 x 300mm
- Bond: Stretcher
- Installation: Dry laid, without a mortar joint, so vertical & horizontal voids are aligned. Insulation to outside
- Concrete Fill: to BS EN 206 - flow class not higher than F5
 - Concrete: C30 or to Engineers specification
 - Slump between 180-220mm
 - Width of concrete fill: 120mm
 - Reinforcement: To engineer's drawings

Wood-Cement Permanent Formwork Walling Units

Manufacturer: Durisol UK Ltd
Parkway, Pen-Y-Fan Industrial Estate, Crumlin,
NP11 3EL
01495 249400

Product reference: D250

- Thermal conductivity (maximum) certified by UKAS accredited laboratory at BM TRADA – U0.82
- Work sizes (length x height x thickness): 500 x 250 x 250mm
- Bond: Stretcher
- Installation: Dry laid, without a mortar joint, so vertical & horizontal voids are aligned.
- Concrete Fill: to BS EN 206 - flow class not higher than F5
 - concrete: C30 or to Engineers specification
 - Slump between 180-220mm
 - width of concrete fill: 180mm
 - Reinforcement: To engineer's drawings

Wood-Cement Permanent Formwork Walling Units

Manufacturer: Durisol UK Ltd
Parkway, Pen-Y-Fan Industrial Estate, Crumlin,
NP11 3EL
01495 249400

Product reference: D170.

- Thermal conductivity (maximum) certified by UKAS accredited laboratory at BM TRADA – U1.1
- Work sizes (length x height x thickness): 500 x 250 x 170mm
- Bond: Stretcher
- Installation: Dry laid, without a mortar joint, so vertical & horizontal voids are aligned.
- Concrete Fill: to BS EN 206 - flow class not higher than F5
 - concrete: C30 or to Engineers specification
 - Slump between 180-220mm
 - width of concrete fill: 120mm
 - Reinforcement: To engineer's drawings